







レギュラー






■特長と用途

塩ビ鋼板、スパンドレル等薄鉄板と鉄下地への締結





品番	サイズ (mm)	入数	D (mm)	L (mm)	EL (mm)	SL	ねじピッチ	d (mm)	t (mm)	十字穴	適応板厚 (mm)	JAN
P-3510	3.5×10	15,000本 (1,500本×10箱)	3.5	10	3							4516166001790
P-3513	3.5×13	10,000本 (1,000本×10箱)	3.5	13	6	全ねじ	1.3	7.0	2.5	No.2	0.9~2.3	4516166001806
*P-3516	3.5×16	10,000本 (1,000本×10箱)	3.5	16	9	土化	(20川)	7.0		140.	0.0 2.0	4516166001813
*P-3519	3.5×19	10,000本 (1,000本×10箱)	3.5	19	12							4516166001820
P-4010	4×10	10,000本 (1,000本×10箱)	4.2	10	3						1.2~2.3	4516166001844
P-4013	4×13	10,000本 (1,000本×10箱)	4.2	13	4							4516166001851
P-4016	4×16	10,000本 (1,000本×10箱)	4.2	16	7							4516166001868
P-4019	4×19	10,000本 (1,000本×10箱)	4.2	19	10							4516166001875
P-4025	4×25	5,000本(500本×10箱)	4.2	25	16							4516166001882
P-4030	4×30	5,000本(500本×10箱)	4.2	30	21	全ねじ	1.4 (18山)	8.0	3.0	No.2	1.2~3.2	4516166001899
*P-4035	4×35	2,500本(500本× 5箱)	4.2	35	25	全ねじ	(тощ)					4516166001905
*P-4040	4×40	2,500本(500本×5箱)	4.2	40	30							4516166001912
*P-4045	4×45	2,500本(500本×5箱)	4.2	45	35							4516166001929
*P-4050	4×50	2,500本(500本×5箱)	4.2	50	40							4516166001936
*P-4060	4×60	2,500本(500本× 5箱)	4.2	60	50							4516166001943
P-5013	5×13	5,000本(500本×10箱)	4.8	13	4							4516166001950
P-5016	5×16	5,000本(500本×10箱)	4.8	16	6							4516166001967
P-5019	5×19	5,000本(500本×10箱)	4.8	19	9		1.6					4516166001974
*P-5025	5×25	5,000本(500本×10箱)	4.8	25	15	全ねじ	(16山)	9.5	3.5	No.2	1.6~3.5	4516166001981
*P-5030	5×30	2,500本(500本× 5箱)	4.8	30	20		() - ,					4516166001998
*P-5035	5×35	2,500本(500本× 5箱)	4.8	35	25							4516166002001
*P-5045	5×45	2,500本(500本×5箱)	4.8	45	35							4516166002018
*P-6019	6×19	2,500本(500本× 5箱)	6.3	19	6	全ねじ	1.8	13.0	1 F	No.3	2.3~4.5	4516166002025
*P-6025	6×25	2,500本(500本× 5箱)	6.3	25	11	±180	(14山)	13.0	4.0	110.3	2.3.~4.5	4516166002032














■特長と用途

塩ビ鋼板、スパンドレル等薄鉄板と鉄下地への締結





品番	サイズ (mm)	入数	D (mm)	L (mm)	EL (mm)	SL	ねじピッチ	d (mm)	t (mm)	十字穴	適応板厚 (mm)	JAN
*PS-3510	3.5×10	15,000本 (1,500本×10箱)	3.5	10	3		1.0					4516166002131
*PS-3513	3.5×13	10,000本 (1,000本×10箱)	3.5	13	6	全ねじ	1.3 (20山)	7.0	2.5	No.2	0.9~2.3	4516166002148
*PS-3516	3.5×16	10,000本 (1,000本×10箱)	3.5	16	9		(20Д)					4516166002155
PS-4010	4×10	10,000本 (1,000本×10箱)	4.2	10	3						1.2~2.3	4516166002186
PS-4013	4×13	10,000本 (1,000本×10箱)	4.2	13	4							4516166002193
PS-4016	4×16	10,000本(1,000本×10箱)	4.2	16	7							4516166002209
PS-4019	4×19	10,000本(1,000本×10箱)	4.2	19	10							4516166002216
PS-4025	4×25	5,000本(500本×10箱)	4.2	25	16	全ねじ	1.4	8.0	3.0	No.2	1.2~3.2	4516166002223
PS-4030	4×30	5,000本(500本×10箱)	4.2	30	21		(18山)	0.0	0.0			4516166002230
*PS-4035	4×35	2,500本(500本× 5箱)	4.2	35	25							4516166002247
PS-4040	4×40	2,500本(500本× 5箱)	4.2	40	30							4516166002254
*PS-4050	4×50	2,500本(500本×5箱)	4.2	50	40							4516166002261
*PS-4060	4×60	2,500本(500本×5箱)	4.2	60	50							4516166002285
PS-5013	5×13	5,000本(500本×10箱)	4.8	13	4							4516166002292
PS-5016	5×16	5,000本(500本×10箱)	4.8	16	6							4516166002308
PS-5019	5×19	5,000本(500本×10箱)	4.8	19	9							4516166002315
PS-5025	5×25	5,000本(500本×10箱)	4.8	25	15		1.0					4516166002322
*PS-5030	5×30	2,500本(500本×5箱)	4.8	30	20	全ねじ	1.6 (16山)	9.5	3.5	No.2	1.6~3.5	4516166002339
*PS-5035	5×35	2,500本(500本×5箱)	4.8	35	24	土480	(, СД)					4516166002346
*PS-5040	5×40	2,500本(500本×5箱)	4.8	40	29							4516166002353
*PS-5050	5×50	2,500本(500本×5箱)	4.8	50	41							4516166002377
*PS-5060	5×60	2,000本(400本×5箱)	4.8	60	51							4516166002384









アルミ材同士や、樹脂、アルミ下地への締結






■特長と用途



並目ねじ山





8

品番	サイズ (mm)	入数	D (mm)	L (mm)	EL (mm)	SL	ねじピッチ	d (mm)	t (mm)	十字穴	使用相手材	JAN
P3S-4013	4×13	10,000本(1,000本×10箱)	4.2				3 4					4516166002629
*P3S-4016	4×16	10,000本(1,000本×10箱)	4.2	16	7	全ねじ	1.4 (18山)	8.0	3.0	No.2	アルミ・樹脂専用	4516166002636
*P3S-4019	4×19	10,000本 (1,000本×10箱)	4.2	19	11		(тощ)				47/13	4516166002643

^{*}の製品につきましては、在庫確認のお問い合せをお願い致します。 ※頭部ペイント、その他表面処理、小袋入加工も別途承ります。

^{*}の製品につきましては、在庫確認のお問い合せをお願い致します。 ※頭部ペイント、その他表面処理、小袋入加工も別途承ります。







ナベ

■特長と用途

屋外環境で、より防錆の要求される箇所への使用[スズめっき] サッシ等の建材に色調を合わせる箇所への使用 「ブロンズ処理·SSブラック処理]











1	ねじ山	١
	並目ねじ山	
		•

品番	サイズ (mm)	入数	D (mm)	L (mm)	EL (mm)	SL	ねじピッチ	d (mm)	t (mm)	十字穴	適応板厚 (mm)	JAN
*PS-4013-S		10,000本(1,000本×10箱)										4516166002476
*PS-4016-S	4×16	10,000本 (1,000本×10箱)	4.2	16	7	全ねじ	1.4 (18山)	8.0	3.0	No.2	1.2~3.2	4516166002483
*PS-4019-S		10,000本 (1,000本×10箱)					(тощ)					4516166002490







(ねじ山
ŀ	並目ねじ山

品番	サイズ (mm)	入数	D (mm)	L (mm)	EL (mm)	SL	ねじピッチ	d (mm)	t (mm)	十字穴	適応板厚 (mm)	JAN
*PS-4013-B	4×13	10,000本 (1,000本×10箱)	4.2	13	4		1.4					4516166002537
*PS-4016-B	4×16	10,000本 (1,000本×10箱) 10,000本 (1,000本×10箱)	4.2	16	7	全ねじ	(18da)	8.0	3.0	No.2	1.2~3.2	4516166002544
*PS-4019-B	4×19	10,000本 (1,000本×10箱)	4.2	19	10		(тощ)					4516166002551

その他のブロンズ色も別途承ります。









品番	サイズ (mm)	入数	D _(mm)	L (mm)	EL (mm)	SL	ねじピッチ	d (mm)	t (mm)	十字穴	適応板厚 (mm)	JAN
*PS-4013-SBK	4×13	10,000本 (1,000本×10箱)	4.2	13	4		1.4					4516166011621
*PS-4016-SBK	4×16	10,000本 (1,000本×10箱) 10,000本 (1,000本×10箱)	4.2	16	7	全ねじ	1.4 (18da)	8.0	3.0	No.2	1.2~3.2	4516166011638
*PS-4019-SBK	4×19	10,000本 (1,000本×10箱)	4.2	19	10		(тощ)					4516166016817

★は、受注処理品
















■特長と用途

アルミ材同士や、アルミ材と鉄下地への締結





品番	サイズ (mm)	入数	D (mm)	L (mm)	EL (mm)	SL	ねじピッチ	d (mm)	t (mm)	十字穴	適応板厚 (mm)	JAN
*PS-4010M	4×10	10,000本 (1,000本×10箱)	4	10	3							4516166002575
*PS-4013M	4×13	10,000本(1,000本×10箱)	4	13	4	A41"	0.7	0 0	20	No 2	1.2~2.3	4516166002582
*PS-4016M	4×16	10,000本 (1,000本×10箱)	4	16	7	全ねじ	(36川)	0.0	3.0	NU.Z	1.2 2.3	4516166002599
*PS-4019M	4×19	10,000本 (1,000本×10箱)	4	19	10							4516166002605













ニュートラス

■特長と用途

金属サイディング、スパンドレル等と鉄下地への締結






品番	サイズ (mm)	入数	D (mm)	L (mm)	EL (mm)	SL	ねじピッチ	d (mm)	t (mm)	十字穴	適応板厚 (mm)	JAN
NT-4013	4×13	10,000本 (1,000本×10箱)	4.2	13	4							4516166000014
NT-4016	4×16	10,000本(1,000本×10箱)	4.2	16	7		1.4					4516166000021
*NT-4019	4×19	5,000本(500本×10箱)	4.2	19	10	全ねじ	1.4 (18山)	11.0	2.7	No.2	1.2~3.2	4516166000038
*NT-4025	4×25	5,000本(500本×10箱)	4.2	25	16		(18Щ)					4516166000045
*NT-4030	4×30	5,000本(500本×10箱)	4.2	30	21							4516166000052
























フラットニュートラス

■特長と用途

看板等、薄鋼板同士の締結





品番	サイズ (mm)	入数	D (mm)	L (mm)	EL (mm)	SL	ねじピッチ	d (mm)	t (mm)	十字穴	適応板厚 (mm)	JAN
MTF-4013T	4×13	10,000本 (1,000本×10箱)	4.2	13	4	全ねじ	1.3(20山)	11.0	2.0	No.2	0.9~2.3	4516166003862

^{*}の製品につきましては、在庫確認のお問い合せをお願い致します。 ※頭部ペイント、その他表面処理、小袋入加工も別途承ります。

^{*}の製品につきましては、在庫確認のお問い合せをお願い致します。 ※頭部ペイント、その他表面処理、小袋入加工も別途承ります。














シンワッシャー モドトラス

■特長と用途

金属サイディング、スパンドレル等と鉄下地への締結



	品番	サイズ (mm)	入数	D (mm)	L (mm)	EL (mm)	SL	ねじピッチ	d (mm)	t (mm)	十字穴	適応板厚 (mm)	JAN
N	MT-4013	4×13	10,000本(1,000本×10箱)	4.2	13	4							4516166000175
I	MT-4016	4×16	10,000本 (1,000本×10箱)	4.2	16	7	全ねじ	1.4	110	25	No 2	1.2~3.2	4516166000182
I	MT-4019	4×19	5,000本(500本×10箱)	4.2	19	10	±100	(18山)	11.0	2.0	NO.L	1.2 0.2	4516166000199
* [MT-4025	4×25	5,000本(500本×10箱)	4.2	25	16							4516166000205



11















■特長と用途

金属サイディング、スパンドレル等と鉄下地への締結



Ė	品番	サイズ (mm)	入数	(mm)	(mm)	EL (mm)	SL	ねじピッチ (mm)	d (mm)	t (mm)	十字穴	適応板厚 (mm)	JAN
* NW-5	5035	5×35	2,500本 (500本× 5箱)	4.8	35	24							4516166000229
* NW-5	5040	5×40	2,000本 (400本× 5箱)	4.8	40	29	4.0						4516166000236
* NW-5	5045	5×45	1,500本 (300本× 5箱)	4.8	45	34							4516166000243
* NW-5	5050	5×50	1,500本 (300本× 5箱)	4.8	50	39	8.0						4516166000250
* NW-5	5060	5×60	1,500本 (300本× 5箱)	4.8	60	49	18.0	1.6	12.0	20	No.2	1.6~3.5	4516166000267
* NW-5	5070	5×70	1,250本 (250本× 5箱)	4.8	70	59	28.0	(16山)	12.0		IVOIL	1.0 0.0	4516166000274
* NW-5	5075	5×75	1,250本 (250本× 5箱)	4.8	75	64	33.0						4516166000281
* NW-5	5080	5×80	1,000本 (200本× 5箱)	4.8	80	69	38.0						4516166000298
* NW-5	5090	5×90	1,000本 (200本× 5箱)	4.8	90	79	33.0						4516166000304
* NW-5	50100	5×100	1,000本 (200本× 5箱)	4.8	100	89	43.0						4516166000311



※ステンレス製及び、その他サイズも別途承ります。












サラ

■特長と用途

座ぐり金具、軟質木材と鉄下地への締結



品番	サイズ (mm)	入数	(mm)	L (mm)	EL (mm)	SL	ねじピッチ	d (mm)	t (mm)	十字穴	適応板厚 (mm)	JAN
*F-3513	3.5×13	15,000本 (1,500本×10箱)	3.5	13	6							4516166002711
F-3516	3.5×16	10,000本(1,000本×10箱)	3.5	16	9	全ねじ	1.3	70	2.5	No.2	0.9~2.3	4516166002728
*F-3519	3.5×19	10,000本(1,000本×10箱)	3.5	19	12	土1なし	(20山)	7.0	2.0	NO.E	0.5 - 2.5	4516166002667
*F-3525	3.5×25	10,000本(1,000本×10箱)	3.5	25	18							4516166002674
*F-4010	4×10	15,000本 (1,500本×10箱)	4.2	10	3						1.2~2.3	4516166002735
F-4013	4×13	10,000本(1,000本×10箱)	4.2	13	4						1.2~2.3	4516166002681
F-4016	4×16	10,000本(1,000本×10箱)	4.2	16	7							4516166002698
F-4019	4×19	10,000本(1,000本×10箱)	4.2	19	10							4516166002742
F-4025	4×25	5,000本(500本×10箱)	4.2	25	16		1.4					4516166002759
F-4030	4×30	5,000本(500本×10箱)	4.2	30	21	全ねじ	(18山)	8.0	2.7	No.2		4516166002766
F-4035	4×35	2,500本(500本×5箱)	4.2	35	25		(тощ)				1.2~3.2	4516166002773
F-4040	4×40	2,500本(500本×5箱)	4.2	40	30							4516166002704
F-4050	4×50	2,500本(500本×5箱)		50	40							4516166002797
*F-4060	4×60	2,000本(400本×5箱)	4.2	60	50							4516166002803
*F-4065	4×65	2,000本(400本× 5箱)	4.2	65	55							4516166002810
*F-5019	5×19	5,000本(500本×10箱)	4.8	19	9							4516166002834
*F-5025	5×25	5,000本(500本×10箱)	4.8	25	15							4516166002841
*F-5030	5×30	2,500本(500本×5箱)	4.8	30	20							4516166002858
*F-5035	5×35	2,500本(500本×5箱)	4.8	35	25	全ねじ	1.6					4516166002865
*F-5040	5×40	2,500本(500本×5箱)	4.8	40	30	主100))	(16山)	9.0	3.0	No.2	1.6~3.5	4516166002872
*F-5050	5×50	2,500本(500本×5箱)	4.8	50	40							4516166002896
*F-5060	5×60	2,000本(400本×5箱)	4.8	60	50							4516166002902
*F-5070	5×70	2,000本(400本× 5箱)	4.8	70	60							4516166002919
*F-5080	5×80	2,000本(400本× 5箱)	4.8	80	70	13.0						4516166002926



* FS-5070



5×70 2,000本(400本×5箱) 4.8 70 60



品番	サイズ (mm)	入数	D _(mm)	L (mm)	EL (mm)	SL	ねじピッチ	d (mm)	t (mm)	十字穴	適応板厚 (mm)	JAN
* FS-4010	4×10	15,000本 (1,500本×10箱)	4.2	10	3						1.2~2.3	4516166003053
FS-4013	4×13	10,000本 (1,000本×10箱)	4.2	13	4						1.2 2.0	4516166003060
FS-4016	4×16	10,000本 (1,000本×10箱)	4.2	16	7							4516166003077
FS-4019	4×19	10,000本 (1,000本×10箱)	4.2	19	10		1.4					4516166003084
FS-4025	4×25	5,000本(500本×10箱)	4.2	25	16	全ねじ	(18山)	8.0	2.7	No.2		4516166003091
FS-4030	4×30	5,000本(500本×10箱)	4.2	30	21		(тощ)				1.2~3.2	4516166003107
* FS-4040	4×40	2,500本(500本×5箱)	4.2	40	30							4516166003121
* FS-4045	4×45	2,500本(500本×5箱)	4.2	45	35							4516166003138
* FS-4050	4×50	2,500本(500本×5箱)	4.2	50	40							4516166003145
*FS-5019	5×19	5,000本(500本×10箱)	4.8	19	9							4516166003152
* FS-5025	5×25	5,000本(500本×10箱)	4.8	25	15							4516166003169
* FS-5030	5×30	2,500本(500本× 5箱)	4.8	30	20							4516166003176
* FS-5035	5×35	2,500本(500本×5箱)	4.8	35	25	全わじ	1.6	90	3.0	No.2	1.6~3.5	4516166003183
* FS-5045	5×45	2,500本(500本×5箱)	4.8	45	35	全ねじ	(16山)	0.0	0.0		1.0 0.0	4516166003190
* FS-5050	5×50	2,500本(500本×5箱)	4.8	50	40							4516166003206
* FS-5060	5×60	2,000本(400本× 5箱)	4.8	60	50							4516166003213

並目ねじ山

4516166003220

^{*}の製品につきましては、在庫確認のお問い合せをお願い致します。

[※]頭部ペイント、その他表面処理、小袋入加工も別途承ります。

[※]アルミ、樹脂材用SUS 305J1ステンレス製も別途承ります。(鋼板使用不可)
















■特長と用途

軽鉄下地とC型鋼の締結



品番	サイズ (mm)	入数	D (mm)	L (mm)	EL (mm)	SL	ねじピッチ	d (mm)	t (mm)	十字穴	適応板厚 (mm)	JAN
*W-4010T	4×10	15,000本 (1,500本×10箱)	4.2	10	3							4516166385425
*W-4013T	4×13	15,000本 (1,500本×10箱)	4.2	13	4	Ahli	1.4	6.0	1.8	No 2	1.2~2.3	4516166385432
*W-4016T	4×16	10,000本 (1,000本×10箱)	4.2	16	7	全ねじ	(18山)	6.0	1.0	110.∠	1.2~2.3	4516166385449
*W-4019T	4×19	10,000本 (1,000本×10箱)	4.2	19	10							4516166385456
















■特長と用途

サッシ等アルミ建材と鉄下地への締結



品番	サイズ (mm)	入数	D (mm)	L (mm)	EL (mm)	SL	ねじピッチ (mm)	d (mm)	t (mm)	十字穴	適応板厚 (mm)	JAN
WS-4010T	4×10	15,000本 (1,500本×10箱)	4.2	10	3							4516166003404
WS-4013T	4×13	15,000本 (1,500本×10箱)	4.2	13	4		1.4					4516166003411
WS-4016T	4×16	10,000本 (1,000本×10箱)	4.2	16	7	全ねじ	(18III)	6.0	1.8	No.2	1.2~2.3	4516166003428
WS-4019T	4×19	10,000本 (1,000本×10箱)	4.2	19	10		(тощ)					4516166003435
*WS-4025T	4×25	10,000本 (1,000本×10箱)	4.2	25	16							4516166003442












13



■特長と用途


サッシ等アルミ建材と鉄下地への締結



品番	サイズ (mm)	入数	D (mm)	L (mm)	EL (mm)	SL	ねじピッチ	d (mm)	t (mm)	十字穴	適応板厚 (mm)	JAN
WS-4010M	4×10	15,000本(1,500本×10箱)	4	10	3							4516166003350
WS-4013M	4×13	15,000本(1,500本×10箱)	4	13	4		0.7					4516166003367
WS-4016M	4×16	10,000本(1,000本×10箱)	4	16	7	全ねじ		6.0	1.5	No.2	1.2~1.6	4516166003374
WS-4019M	4×19	10,000本(1,000本×10箱)	4	19	10		(36川)					4516166003381
*WS-4025M	4×25	10,000本(1,000本×10箱)	4	25	16							4516166003398

ねじ長さ選定方法

※取付相手材 木毛セメント板・サイディング材等 ※カタログ上の表現の為リーマ部が残っ ていますが、本来は飛散します。










並目ねじ山

サラ (D=7)

■特長と用途

サッシ等アルミ建材と鉄下地への締結



品番	サイズ (mm)	入数	D (mm)	L (mm)	EL (mm)	SL	ねじピッチ	d (mm)	t (mm)	十字穴	適応板厚 (mm)	JAN
FS-4013XD7	4×13	10,000本(1,000本×10箱)	4.2	13	4						1.2~2.3	4516166004203
*FS-4016XD7	4×16	10,000本(1,000本×10箱)	4.2	16	7							4516166020401
*FS-4019XD7	4×19	10,000本(1,000本×10箱) 5,000本(500本×10箱)	4.2	19	10	会わげ	1.4 (18山)	7.0	23	No 2	1.2~3.2	4516166020159
*FS-4025XD7	4×25	5,000本(500本×10箱)	4.2	25	16	土140	(18山)	7.0	2.0	110.2	1.2~3.2	4516166004210
FS-4030XD7	4×30	5,000本(500本×10箱)	4.2	30	21		(тош)					4516166004227
*FS-4035XD7	4×35	2,500本(500本× 5箱)	4.2	35	25							4516166004234












■特長と用途

窯業系サイディング、硬質木質建材と鉄下地への締結




品番	サイズ (mm)	入数	D (mm)	L (mm)	EL (mm)	SL	ねじピッチ	d (mm)	t (mm)	十字穴	適応板厚 (mm)	JAN
*R-4028	4×28	5,000本 (500本×10箱)	4.2	28	13							4516166000410
R-4032	4×32	5,000本 (500本×10箱)	4.2	32	17		1.4					4516166000427
R-4040	4×40	2,500本 (500本× 5箱)	4.2	40	25	5	(18山)	8.0	2.7	No.2	1.6~3.2	4516166000441
R-4045	4×45	2,500本 (500本× 5箱)	4.2	45	30		(тощ)					4516166000458
R-4050	4×50	2,500本 (500本× 5箱)	4.2	50	35							4516166000465
*R-5040	5×40	2,500本 (500本× 5箱)	4.8	40	25							4516166000472
*R-5045	5×45	2,500本 (500本× 5箱)	4.8	45	30	4.5						4516166000489
*R-5050	5×50	2,500本 (500本× 5箱)	4.8	50	35							4516166000496
*R-5060	5×60	2,000本 (400本× 5箱)	4.8	60	45	13	1.6					4516166000502
*R-5070	5×70	1,500本 (300本× 5箱)	4.8	70	55	10	1.6 (16山)	9.0	3.0	No.2	1.6~3.5	4516166000519
*R-5075	5×75	1,000本 (200本× 5箱)	4.8	75	60	18	(тощ)					4516166385616
*R-5090	5×90	1,000本 (200本× 5箱)	4.8	90	75	33						4516166385623
*R-50100	5×100	1,000本 (200本× 5箱)	4.8	100	85	43						4516166385630
*R-50115	5×115	1,000本 (200本× 5箱)	4.8	115	100	58						4516166385647







ねじ山



^{*}の製品につきましては、在庫確認のお問い合せをお願い致します。

[※]頭部ペイント、その他表面処理、小袋入加工も別途承ります。

15
















六角座付

■特長と用途

サイディング、折板と鉄下地への締結



品番	サイズ (mm)	入数	D (mm)	L (mm)	EL (mm)	SL (mm)	ねじピッチ	d (mm)	h (mm)	S (mm)	適応板厚 (mm)	JAN
* H-5013	5×13	5,000本 (1,000本×5箱)	4.8	13	4						1.6~3.5	4516166000779
H-5016	5×16	5,000本 (1,000本×5箱)	4.8	16	6							4516166000786
H-5019	5×19	5,000本 (1,000本×5箱)	4.8	19	9							4516166000793
H-5025	5×25	2,500本(500本×5箱)	4.8	25	15	全ねじ	1.6	11.0	47	8.0	1.6~4.0	4516166000809
* H-5035	5×35	2,500本(500本×5箱)	4.8	35	25	±100	(16山)		,	0.0	110 110	4516166000823
* H-5045	5×45	1,500本(300本×5箱)	4.8	45	35							4516166000847
* H-5050	5×50	1,500本(300本×5箱)	4.8	50	40							4516166000854
* H-5065	5×65	1,500本(300本×5箱)	4.8	65	55							4516166000878
H-6019	6×19	2,500本(500本×5箱)	6.3	19	6						2.3~4.5	4516166000885
H-6025	6×25	2,000本(400本×5箱)	6.3	25	11							4516166000892
* H-6030	6×30	1,500本(300本×5箱)	6.3	30	16							4516166000908
* H-6035	6×35	1,500本(300本×5箱)	6.3	35	20	全ねじ						4516166000915
* H-6040	6×40	1,500本(300本×5箱)	6.3	40	25							4516166000922
* H-6045	6×45	1,500本(300本×5箱)	6.3	45	30							4516166000939
* H-6050	6×50	1,500本(300本×5箱)	6.3	50	35							4516166000946
* H-6060	6×60	1,000本(200本×5箱)	6.3	60	45	10.0						4516166000953
* H-6070	6×70	1,000本(200本×5箱)	6.3	70	55	15.0	1.8	13.0	65	9.5	2.3~6.0	4516166000960
* H-6075	6×75	1,000本(200本×5箱)	6.3		60	20.0	(14山)	10.0	0.0	0.0	2.0 0.0	4516166000977
* H-6090	6×90	1,000本(200本×5箱)	6.3		75	30.0						4516166000984
* H-60105	6×105	500本(100本×5箱)	6.3	105	90	45.0						4516166000991
* H-60115	6×115	500本(100本×5箱)				0 55.0						4516166001004
* H-60135	6×135	500本(100本×5箱)	6.3	135	120	65.0						4516166001011
* H-60150	6×150	500本(100本×5箱)	6.3	150	135	65.0						4516166001028












六角座付

■特長と用途

サイディング、折板と鉄下地への締結



品番	サイズ (mm)	入数	D (mm)	L (mm)	EL (mm)	SL (mm)	ねじピッチ	d (mm)	h (mm)	S (mm)	適応板厚 (mm)	JAN
*HS-5013	5×13	5,000本 (1,000本×5箱)	4.8	13	4						1.6~3.5	4516166001110
*HS-5016	5×16	5,000本 (1,000本×5箱)	4.8	16	6							4516166001127
HS-5019	5×19	5,000本 (1,000本×5箱)	4.8	19	9							4516166001134
HS-5025	5×25	2,500本(500本×5箱)	4.8	25	15	全ねじ	1.6 (16山)	11.0	4.7	8.0	1.6~4.0	4516166001141
* HS-5030	5×30	2,500本(500本×5箱)	4.8	30	20		(тощ)					4516166001158
* HS-5035	5×35	2,500本(500本×5箱)	4.8	35	25							4516166001165
* HS-5045	5×45	1,500本(300本×5箱)	4.8	45	35							4516166001189
HS-6019	6×19	2,500本(500本×5箱)	6.3	19	6						2.3~4.5	4516166001325
HS-6025	6×25	2,000本(400本×5箱)	6.3	25	11							4516166001332
*HS-6030	6×30	1,500本(300本×5箱)	6.3	30	16							4516166001349
* HS-6035	6×35	1,500本(300本×5箱)	6.3	35	20	全ねじ						4516166001356
*HS-6040	6×40	1,500本(300本×5箱)	6.3	40	25							4516166001363
* HS-6045	6×45	1,500本(300本×5箱)	6.3	45	30		1.8 (14山)	13.0	6.5	9.5	2.3~6.0	4516166001370
* HS-6050	6×50	1,500本(300本×5箱)	6.3	50	35		(т-тщ)					4516166001387
* HS-6060	6×60	1,000本(200本×5箱)	6.3	60	45	10.0						4516166001394
* HS-6070	6×70	1,000本(200本×5箱)	6.3	70	55	15.0						4516166001400
* HS-6075	6×75	1,000本(200本×5箱)	6.3	75	60	20.0						4516166001417
* HS-6090	6×90	1,000本(200本×5箱)	6.3	90	75	30.0						4516166001424














厚鋼用

六角座付ポイント5

■特長と用途

鉄板厚が6.0ミリを超える箇所への締結



	品番	サイズ (mm)	入数	D (mm)	L (mm)	EL (mm)	SL (mm)	ねじピッチ	d (mm)	h (mm)	S (mm)	適応板厚 (mm)	JAN
H5	-5532	5.5×32	2,500本(500本×5箱)	5.5	32	11							4516166001547
H5	-5538	5.5×38	2,500本(500本×5箱)	5.5	38	17	全ねじ						4516166001554
* H5	-5550	5.5×50	1,500本(300本×5箱)	5.5	50	29		1.0	110	5.0	8.0	6.0~12.5	4516166001561
* H5	-5565	5.5×65	1,500本(300本×5箱)	5.5	65	44	6.0 13.0	(24山)	11.0	5.0	0.0	6.0~12.5	4516166001578
* H5	5-5580	5.5×80	1,000本(200本×5箱)	5.5	80	59							4516166001585
* H5	-5590	5.5×90	1,000本(200本×5箱)	5.5	90	69	23.0						4516166001592

stの製品につきましては、在庫確認のお問い合せをお願い致します。

[※]その他表面処理、シーリング・ワッシャー組込も別途承ります。















防水ワッシャー付





サイディング、折板屋根等と鉄下地への締結



品番	サイズ (mm)	入数	D _(mm)	L (mm)	EL (mm)	SL	ねじピッチ	d (mm)	WH (mm)	S (mm)	適応板厚 (mm)	JAN
* H-5019SW	5×19	2,500本 (500本×5箱)	4.8	19	7							4516166001615
* H-5025SW	5×25	2,500本 (500本×5箱)	4.8	25	13		1.6					4516166001622
* H-5035SW	5×35	2,500本 (500本×5箱)	4.8	35	23	全ねじ	(16山)	13.0	3.5	8.0	1.6~4.0	4516166001639
* H-5045SW	5×45	1,500本 (300本×5箱)	4.8	45	33		(,					4516166001646
* H-5050SW	5×50	1,000本 (200本×5箱)	4.8	50	38							4516166001653
*H-6019SW	6×19	2,000本 (400本×5箱)	6.3	19	4						2.3~4.5	4516166001660
* H-6025SW	6×25	1,500本 (300本×5箱)	6.3	25	9	全ねじ	1.8	16.0	40	9.5	2.3~6.0	4516166001677
* H-6035SW	6×35	1,500本 (300本×5箱)	6.3	35	18		(14山)	10.0	→. ∪	0.0	2.0 -0.0	4516166001684
* H-6045SW	6×45	1,000本 (200本×5箱)	6.3	45	28							4516166001691







並目ねじ山

品番	サイズ (mm)	入数	D (mm)	L (mm)	EL (mm)	SL	ねじピッチ	d (mm)	WH (mm)	S (mm)	適応板厚 (mm)	JAN
* HS-5019SWS	5×19	2,500本 (500本×5箱)	4.8	19	7	全ねじ	1.6 (16山)	13.0			1.6~4.0	4516166001707
* HS-5025SWS	5×25	2,500本 (500本×5箱)	4.8	25	13				3.5 8	8.0		4516166001714
* HS-5035SWS	5×35	2,500本 (500本×5箱)	4.8	35	23					0.0		4516166001721
* HS-5045SWS	5×45	1,500本 (300本×5箱)	4.8	45	33							4516166001738
*HS-6019SWS	6×19	2,000本 (400本×5箱)	6.3	19	4						2.3~4.5	4516166001752
*HS-6025SWS	6×25	1,500本 (300本×5箱)	6.3	25	9	全ねじ	1.8	100	4.0	0.5	2.3~6.0	4516166001769
*HS-6035SWS	6×35	1,500本 (300本×5箱)	6.3	35	18		(14山)	16.0	4.0	9.5		4516166001776
*HS-6045SWS	6×45	1,000本 (200本×5箱)	6.3	45	28							4516166001783














波板ドリル

SUS304製波板用座金+パッキン付

■特長と用途

ポリカ、塩ビ、鉄板(小波・32波)波板と鉄下地への締結



品番	サイズ (mm)	入数	D (mm)	L (mm)	EL (mm)	H(SL)	ねじピッチ	d (mm)	h (mm)	S (mm)	適応板厚 (mm)	JAN
*HW-5025-R2S	5×25	1,800本(300本×6箱)	4.5	25	15.0	11.0	1.0(24山)	11.0	5.0	8.0	1.6~3.2	4516166003879














スティックビス

■特長と用途

軽鉄スタッドと軽鉄ランナーとの締結





品番	サイズ (mm)	入数	D (mm)	L (mm)	EL (mm)	SL	ねじピッチ	d (mm)	t (mm)	十字穴	適応板厚 (mm)	JAN
*TSD-4213	4.2×13	10,000本(1,000本×10箱)	4.2	13	4	全ねじ	1.41	0 -		No.2	0.6~1.2	4516166385487
*TSD-4216	4.2×16	10,000本 (1,000本×10箱)	4.2	16	7		(2条)	8.5	1.5			4516166385494












スライスヘッド

■特長と用途

鋼板の重ね部分など頭部が緩衝する部分の締結





品番	サイズ (mm)	入数	D (mm)	L (mm)	EL (mm)	SL	ねじピッチ	d (mm)	t (mm)	十字穴	適応板厚 (mm)	JAN
*TSC-5016	5×16	7,000本(700本×10箱)	4.8	16	6	全ねじ	1.6 (16山)	10.0	1.0	No.2	1.6~3.2	4516166385500
*TSC-5019	5×19	7,000本(700本×10箱)	4.8	19	9							4516166385517
* TSC-5025	5×25	5,000本 (500本×10箱)	4.8	25	15							4516166385524
*TSC-5035	5×35	2,500本 (500本× 5箱)	4.8	35	25							4516166385531
* TSC-5045	5×45	2,500本 (500本× 5箱)	4.8	45	35							4516166385548












■特長と用途

鋼板の重ね部分など頭部が緩衝する部分の締結





品番	サイズ (mm)	入数	D (mm)	L (mm)	EL (mm)	SL	ねじピッチ	d (mm)	t (mm)	十字穴	適応板厚 (mm)	JAN
*TSCS-5016	5×16	7,000本 (700本×10箱)	4.8	16	6	全ねじ	1.0	10.0	1.0	No.2	1.6~3.2	4516166385555
*TSCS-5019	5×19	7,000本 (700本×10箱)	4.8	19	9							4516166385562
*TSCS-5025	5×25	5,000本 (500本×10箱)	4.8	25	15		(16III)					4516166385579
*TSCS-5035	5×35	2,500本 (500本× 5箱)	4.8	35	25		(тощ)					4516166385586
*TSCS-5045	5×45	2,500本 (500本× 5箱)	4.8	45	35							4516166385593

^{*}の製品につきましては、在庫確認のお問い合せをお願い致します。 ※その他サイズのシーリング・ワッシャー組込も別途承ります。

^{*}の製品につきましては、在庫確認のお問い合せをお願い致します。 ※その他、表面処理も別途承ります。